

# DD 3050S Weld-in thermowell according to DIN43772 Form 4S

## Thermowell

**Design** Drilled bar stock (solid machined)

**Process connection** Weld-in

## Material

**Stock items** Wst. 1.4571, 1.4404, 1.7335, 1.5415, 1.0460

**Other materials** To specify

## Stem / Shrank

**Wetted part** Tapered

## Dimensions

**Length L1, L2, L3.** See table

**Standard** According DIN 43772 Form 4S

**Bore Size** 3.5mm

**Tolerance** H7

## Options

Other dimensions or bore size

Plug and chain for test wells

Tagging

Wake frequency calculation

Type	L1	L2	L3	D1	D2	Connect.
DS1	115	50	40	18	9	M14x1.5
DS2	140	50	65	18	9	M14x1.5



## Ordering code

\*This datasheet is purely indicative, build-up of model code may vary from this datasheet.

Model DD 3050S

Material

Type

H3-1 Rev.0 7/07



**thermo-electra**  
temperature sensor solutions

Thermo Electra B.V.  
Weteringweg 10  
2641KM Pijnacker  
The Netherlands

Phone +31 (0)15 - 3621200  
Fax +31 (0)15 - 3694082  
Email sales@thermo.nl  
<http://www.thermo-electra.com>

