


CA 2004 Fast response resistance thermometer

Protection tube	
Construction	Closed-end tube
Insertion length	Customer to specify
Material	SS 316 - (Wst 1.4401) standard, other materials possible
Process connection	M20x1.5, 1/2"BSP (G1/2"), 1/2"NPT or other threads possible
Connection head	
Material	Alumimium, plastic or stainless steel
Cable entry	M20x1.5 cable gland standard, other threads possible
Measuring insert	
Construction	Fixed
Tip	Reduced
Stem diameter	9.0mm standard, other diameters possible
Tip diameter	6.0mm standard, other diameters possible
Sensor	
	Single or Duplex Pt100
Accuracy	According IEC60751 class B
Style / Connection	3-wire system, 4-wire system optional
Range	-220 / +600°C
Options	
Transmitter 4-20mA	In-Head transmitter, standard or Ex version. Please select from our standard range or specify your own standard
Swing-Cover head	DAN, transmitter direct mounted on measuring insert
High Swing-Cover head	DAN-H, transmitter in cover, insert with ceramic block



Ordering code

*This datasheet is purely indicative, build-up of model code may vary from this datasheet.

Model	CA 2004		
Sensor (S or D)		↑	↑
Length "L" in mm			↑

H2-1 Rev.0 7/07