

TE1028 Mehrfach-Thermoelementscharttafel horizontal

Application

| | |
|---------------------------|---|
| Female multi panel | Thermocouple and RTD circuits |
| Contacts | Springloaded thermocouple contacts |
| Materials | Glass filled thermocouple body with original thermocouple material contacts |
| Front | Aluminium anodized for full corrosion protection |

Temperature rating

| | |
|--------------------------|---------------|
| Temperature limit | Maximum 200°C |
|--------------------------|---------------|

Construction

| | |
|------------------------|---|
| Body | Glass filled thermoplastic material |
| Design | Stainless steel bracket mounted with 2 screws |
| Molded barriers | Prevent short circuit |
| Identified | Scratchproof numbering |

Wire size

| | |
|----------------------|------------------------|
| Accepts wires | From 0.2 mm to 2.0 mm |
| Colour code | According thermocouple |



Dimensions in mm

| Circuits | Rows | L | H |
|----------|------|-----|-----|
| 1 | 1 | 38 | 38 |
| 6 | 1 | 146 | 67 |
| 12 | 1 | 260 | 67 |
| 24 | 2 | 260 | 115 |

Ordering code

*This datasheet is purely indicative, build-up of model code may vary from this datasheet.

Model

TE 1028

H9-2 Rev. 0 07/07